

CERTIFICATE OF CONSTANCY OF PERFORMANCE

0751-CPR.2-010.4-01

In compliance with Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011 (the Construction Products Regulation or CPR), this certificate applies to the construction product

Factory made mineralwool (MW) products (details cf. annex)

placed on the market by **Rockwool B.V.**
Industrieweg 15
6040 KD Roermond
Netherlands

and produced in the factory **ROCKWOOL Operations GmbH & Co. KG**
Werk Gladbeck
Rockwool Straße 37 – 41
45966 Gladbeck
Germany

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard

EN 14303:2009+A1:2013

under system 1 are applied and that

the essential characteristics of reaction to fire for the products fulfil all the prescribed requirements set out above

This certificate was first issued on 10.03.2016 and will remain valid as long as the test methods and/or factory production control requirements included in the harmonised standard (but no longer than 01.08.2018), used to assess the performance of the declared characteristics, do not change, and the product, and the manufacturing conditions in the plant are not modified significantly.

Gräfelfing, 02.08.2017



Head of Certification Body



Dipl.-Ing. (FH) Wolfgang Albrecht

Factory: ROCKWOOL Operations GmbH & Co. KG Werk Gladbeck, Rockwool Straße 37 – 41, 45966 Gladbeck , Germany

Construction product(s): Factory made mineralwool (MW) products according to EN 14303:2009+A1:2013

Intended use: Thermal insulation products for building equipment and industrial installations

Level(s) or class(es) reaction to fire: for uses subject to regulations on reaction to fire A1/A2/B. Products for which a clearly identifiable stage in the production process results in an improvement of the classification by limiting of organic material.

Attestation of conformity system: 1

No.	Product		Reaction to fire EN 13501-1				
	Form	Type	Description	Classification	Range	Report. No	Classification report
1	Lamella mat	Rockwool 133 EF	Non- combustible mineral wool lamella mat onto reinforced aluminium foil with self-adhesive layer on the wool side	B-s1,d0	Thickness: ≤ 20 mm to < 40 mm Density: 37 kg/m ³	1	RA15-0214
2	Lamella mat	Rockwool 133 EF	Non- combustible mineral wool lamella mat onto reinforced aluminium foil with self-adhesive layer on the wool side	A2-s1,d0	Thickness: ≤ 40 mm to ≤ 50 mm Density: 37 kg/m ³	2	RA15-0214
3	Lamella mat	Rockwool 133	Non- combustible mineral wool lamella mat onto reinforced aluminium foil	A1	Thickness: ≤ 25 mm to ≤ 100 mm	3	230008253-4
4	Lamella mat	Teclit LM200-Cold	Non- combustible mineral wool lamella mat onto reinforced aluminium foil	A2-s1,d0	Thickness: ≤ 20 mm to ≤ 50 mm Density: 45 kg/m ³ ± 15 %	4	230010468-3

Detail information about the insulation products are given in the classification reports
 Gräfelfing 02.08.2017



Head of Certification Body



Dipl.-Ing. (FH) Wolfgang Albrecht